

## Baler, hydraulic presse PAAL Konti 275 D

### Technical specification

<b>Max. pressure:</b>	75 tons	<b>Year of production:</b>	1999
<b>Unit pressure:</b>	90,9 t/m <sup>2</sup>	<b>Number of strappings:</b>	4 in vertikal
<b>Cross-section of the channel:</b>	750 x 1100 mm	<b>Filling inlet:</b>	1020 x 1550 mm
<b>Bale weight:</b>	500-750 kg	<b>Weight:</b>	ca. 25 tons
<b>Supply:</b>	400 V	<b>Bale tying:</b>	automatic, wire

Efficiency on idle: max 750 m<sup>3</sup> / h

Efficiency under load: max 350 m<sup>3</sup> / h

Theoretical efficiency with material in density 35 kg/m<sup>3</sup>) 12 tons/h

Theoretical efficiency with material in density 60 kg/m<sup>3</sup>) 21 tons/h

Theoretical efficiency with material in density 100 kg/m<sup>3</sup>) 33 tons/h


#### A short description of functions:

- Open charging hole allows the filling with the conveyor belt .
- Knives on the press plate and frame of the baler to cut off the excess material
- Automatic regulation of the light of the channel
- Automatic bale tying with the wire
- Choosing the length of the finished bale from the operator panel
- Pressing plate which is stable carried on the big rolls
- Big flops of the press chamber for easier maintenance



Zdjęcia poglądowe

### Nasze instalacje



**Masz pytania zadzwoń +48 33 816 01 69**

**Więcej maszyn na [www.belowniceuzywane.pl](http://www.belowniceuzywane.pl)**

ARTechnic  
ul. Gen. St. Maczka 9  
43-300 Bielsko-Biała, POLAND

INFOLINIA: 801 000 816  
tel.: +48 33 816 01 69  
fax: +48 33 443 20 46

[www.artechnic.pl](http://www.artechnic.pl)  
[www.belowniceuzywane.pl](http://www.belowniceuzywane.pl)  
[biuro@artechnic.pl](mailto:biuro@artechnic.pl)